

Torcofix Torque wrench TF-K5 / TF-K25 / TF-K100

- Controlled screw tightening in the range of 1 - 5 Nm / 5 - 25 Nm / 20 - 100 Nm
- Adjustable, releasing and sturdy tubular torque wrench with integrated ratchet and with square drive for industry and the trades
- Classified as per DIN EN ISO 6789-2:2017 Type II Class A; adjusted to a maximum permissible $\pm 3\%$ deviation and thus with a greater precision than the standard-stipulated $\pm 6\%$
- Incl. traceable test certificate (DIN EN ISO 6789-2:2017)
- For controlled right- and left-hand tightening (square socket for direction change)
- mushroom head socket square with ball lock
- Robust, matt powder-coated tubular steel construction, with galvanized ratchet and high-quality plastic parts
- New ergonomic handle, shaped according to the natural grip position of the hand
- clearly recognisable and tactile hand centring aid and calibration aid in the middle of the handle
- Double scale Nm / lbf·ft and vernier are protected from abrasion and contamination by an enlarged viewing window
- Vertical alignment of the scale, torque adjustment therefore suitable for left and right handers
- Scale line positioned directly above the scale prevents reading errors (parallax errors)
- Unit labeling integrated in the scale frame and also protected by viewing windows
- The precise release mechanism generates a distinct tactile and audible release signal when the set torque value is reached

